DECLARATION OF CONFORMITY TTE® PAVERS



- 1. Unique code to identify the product type: Concrete paver
- Intended use(s): Outdoor paving elements
- Manufacturer: HÜBNER-LEE GmbH & Co. KG Gewerbestraße 1 DE-87752 Holzgünz
- 4. System(s) for the assessment and verification of constancy of performance: System 4
- 5. Harmonised standard: EN 1338:2003 und EN 1338:2003/AC:2006
- 6. Declared performance:

Key features	Performance
Reaction to fire	A1
Resistance to external fire	satisfactory
Asbestos emission	No asbestos content
Tensile strength at splitting	\geq 3.6 MPa
Slip resistance/sliding	satisfactory
Coefficient of thermal conductivity	1.42 W/(m*K)
Weather resistance	Class 3 (D)

The performance of the above-mentioned product is in conformity with the declared performance characteristics. This declaration of performance is drawn up in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the above-mentioned manufacturer.

On behalf of the manufacturer, signed: René Hübner - Managing Director

(signature)

Holzgünz, 12 July 2023. (Date and place of issue)

Information on the declaration of use - Status: 12.2023

The declaration of performance applies to the product listed in the table below in all colour variants.

Thickness of the paver	Name of the paver
4.9 cm 5.1 cm	TTE [®] Paver 7.4 x 7.4 x 4.9 cm TTE [®] Paver ^{GRIP} 7.4 x 7.4 x 5.1 cm
Other product features	
Absorption	Class 2 (B) (≤ 6%)
Abrasion resistance	Class 4 (I)
Permissible dimensional deviations: Length and width	± 2 mm
Permissible dimensional deviations: Thickness	± 3mm

The product does not contain any hazardous substances within the meaning of Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006.



HÜBNER-LEE GmbH & Co. KG, Gewerbestr. 1, D-87752 Holzgünz Tel.: +49 8393 9229-0, Fax: -22, info@huebner-lee.eu, www.huebner-lee.de/en

12/23

